

崧羽企業有限公司

多層板片式乾燥機



新北市三峽區介壽路三段 172 巷 21 號

TEL : (02) 8676-3589

FAX : (02) 8676-6207

E-MAIL : sungyeou@gmail.com

多層板片式乾燥機之功能

多層板片式輸送帶可一循環二層乾燥節省上下空間。多層次翻動可增加乾燥均勻度以確保產品品質。輸送機及風車轉速皆採變頻器無段變速

加熱方式:可選擇廠區剩餘熱源, 柴油、蒸氣、電熱、冷凝除濕等方式提供多種選擇配合現場需求。溫度範圍：室溫~+200℃(感溫點為出風口)。

溫度控制：旋鈕數字顯示

風路設計：採用強力多翼式風輪，強力吸風式機構可得到最均勻分佈溫度，安靜低噪音。

出入料方式：連續式出入料產量較批次式乾燥機大且可連結自動化生產線節省人力。

規格說明：

	尺寸(LxWxH)	電壓	風車馬力	輸送機馬力
SA-200	4800×1350×2300 (mm)	AC220V or AC380V	2HP	1HP
SA-240	5500×1350×2300 (mm)		2HP	1HP

備註：進出料段及加熱長度等皆可依客戶要求設計製造。

Multiple Layer Conveyor Dryer



SUNG YEOU ENTERPRISE CO.,LTD.

NO.19 LANE 172 SECTION 3, JIEH RD., SAN XIA
DISTRICT, NEW TAIPEI CITY, TAIWAN R. O. C.

TEL : 00886-2-8676-3589

FAX : 00886-2-8676-6207

E-MAIL : sungyeou@gmail.com

Multiple-Layer conveyor Dryer

The multiple-layer conveyor is designed with a circulating layer and a drying layer so as to save space. Stirring with multiple layers helps to evenly dry materials so as to ensure quality. The rotating speed of conveyor and windmill for warm-up is controlled by a frequency converter at continuously variable speed. The heat resources left at site, diesel, steam, electric heat or de-moisture by cooling are several methods available based on customer's requirements.

Temperature range: room temperature ~ +200°C (the temperature sensor is at the air outlet.)

Thermo control: knob control and digital display

Air channel design: strong fan wheel is adopted. The strong air sucking mechanism creates the most even distribution of temperature. It runs quietly.

Material inlet and outlet: the output by continuous material inlet and outlet is greater than that by lot. The system can be connected with an automatic production line so as to save labors.

Specifications:

	Size (L×W×H)	Voltage	Windmill horsepower	Conveyor horsepower
SA-200	4800×1350×2300 (mm)	AC220V or AC380V	2HP	1HP
SA-240	5500×1350×2300 (mm)		2HP	1HP

Remark: the design for material inlet and outlet section and heating length